

Press Information For Release after January 15, 2003

Editorial & Sales Contact:

Martina Senn
Roboteq, Inc.
1601 E. Sharon Dr
Phoenix, AZ 85022
(602) 549-7535
martina@roboteq.com

Photos available at
www.roboteq.com/press.shtm



At a Glance:

- Dual channel motor controller
- Integrated MOSFET power driver
- 2 x 120Amps at 40V with intelligent current limiting
- RS232 interface
- R/C interface
- User I/Os
- Open loop and closed loop speed mode
- Closed loop position mode
- Field upgradable software

Applications

- Autonomous or remote controlled robotic vehicles
- Underwater robots (ROVs)
- Battlebots
- Underwater robots
- Hazardous material handling, bomb disposal robots
- Surveillance, military, and exploration robots
- Computer controlled DC motors

Roboteq Introduces Smart Dual Channel, 240Amp DC Motor Controller/Driver for Mobile Robots

Phoenix, AZ, January 15, 2003 – Roboteq, Inc (www.roboteq.com) introduces a microcomputer-based dual channel DC motor controller capable of directly driving up to 120Amps on each channel at up to 40V. The AX2500 is targeted at designers of mobile robotic vehicles including Automatic Guided Vehicles (AGV), Underwater Remote Operated Vehicles (ROVs), combat robots (Battlebots) and robots for exploration, hazardous material handling, and military and surveillance applications.

The controller accepts commands from either standard R/C radio for simple remote controlled robot applications or serial port interface. Using the serial port, the AX2500 can be used to design fully or semi-autonomous robots by connecting it to single board computers, wireless modems or wireless LAN adapters.

The controller's two channels can be operated independently or combined to set the direction and rotation of a vehicle by coordinating the motion on each side of the vehicle. The motors may be operated in open or closed loop speed mode. Using

low-cost position sensors, they may also be set to operate as heavy-duty position servos.

The AX2500 features intelligent current sensing and controlling that will automatically limit each channel's power output to 120A for the time typically required to accelerate or stop a robot. If the motor's current draw remains excessive after that time (as in the case of stalled motor or other unusual loading), the controller will gradually reduce the power to user-selected values.

The controller supports a long list of features, including analog and digital I/Os for accessories and sensors, thermal protection, programmable acceleration, input command watchdog and non-volatile storage of configuration parameters.

The AX2500 can be reprogrammed in the field with the latest features by downloading new operating software from Roboteq's web site.

The AX2500 is built into a robust extruded aluminum case, which also serves as a heat sink for its output power stage. The large fin area ensures sufficient heat dissipation for operation without a fan in most applications.

The AX2500 is available now at **\$485** in single quantities, complete with cable and configuration software. Product information, application examples and software can be downloaded from the company's web site at **www.roboteq.com**.

About Roboteq

Founded in 2001 by experts in embedded computing and power electronics, Roboteq's mission is to develop products and technologies that allow novices and professionals alike to build innovative, flexible and affordable mobile robots.

###